

CMS 3 PIN PLUG LEADS

20 amp 3pin plug starter lead with thermal overload mechanism 300mm in from plug. The thermal overload mechanism is designed to cut off power when the lead is overloading to prevent power shortages and hazards.

2 year warranty.

SKU: SW3PINLEADMS

Categories: [Rapid Wiring](#), [Rapid Wiring](#)

20 amp 3pin plug starter lead with thermal overload mechanism 300mm in from plug. The thermal overload mechanism is designed to cut off power when the lead is overloading to prevent power shortages and hazards.

2 year warranty.

PRODUCT DESCRIPTION

1000mm 20A 3 Pin Starter Lead

10A plug to 20amp Tag Installation coupler with Slimline Integrated Thermal Overload. Thermal overload 300mm in from PLUG





2 Year Warranty

GALLERY IMAGES



VARIATIONS

Image	SKU	Stock Status	Stock Quantity	Description	Colour	Size
	SW3PINLEAD1000 BK				Black	1000mm
	SW3PINLEAD1000 WH				White	1000mm
	SW3PINLEAD1500 BK				Black	1500mm
	SW3PINLEAD1500 WH				White	1500mm

Image	SKU	Stock Status	Stock Quantity	Description	Colour	Size
	SW3PINLEAD2000 BK				Black	2000mm
	SW3PINLEAD2000 WH				White	2000mm
	SW3PINLEAD3000 BK				Black	3000mm
	SW3PINLEAD3000 WH				White	3000mm

ADDITIONAL INFORMATION

Weight	0.0000 kg
Dimensions	10 × 1000 × 10 mm
Colour	Black, White
Size	1000mm, 1500mm, 2000mm, 3000mm