



CMS CONDUIT INTERCONNECTING LEADS

Interconnecting lead wrapped in flex plastic conduit with heat shrunk boots. Connect wall and ceiling starters with workstations or connect power between workstations.

Standard interconnecting cables are manufactured from 3 core 2.5mm² flexible cable. They are rated at 20A and are terminated with male and female AS/NZ61535.1 compliant connectors. Where mechanical and EMC segregation from communications cabling is required within furniture and umbilicals, plastic and steel conduit casing with heat shrunk boots are also available. Leads are Halogen Free.

2 year warranty.

ADDITIONAL INFORMATION

Weight	0.0000 kg
Dimensions	10 × 1000 × 10 mm
Colour	Black, White
Size	1000mm, 1500mm, 2000mm, 2500mm, 3000mm, 3500mm, 4000mm, 4500mm, 500mm, 5000mm (5 Meters), 6000mm

SKU: SWCONDUITLEADMS

VARIATIONS

SKU	Colour	Size
SWCONINTLEAD 1000 BK	Black	1000mm
SWCONINTLEAD 1000 WH	White	1000mm
SWCONINTLEAD 1500 BK	Black	1500mm
SWCONINTLEAD 1500 WH	White	1500mm
SWCONINTLEAD 2000 BK	Black	2000mm
SWCONINTLEAD 2000 WH	White	2000mm
SWCONINTLEAD 2500 BK	Black	2500mm
SWCONINTLEAD 2500 WH	White	2500mm
SWCONINTLEAD 3000 BK	Black	3000mm
SWCONINTLEAD 3000 WH	White	3000mm
SWCONINTLEAD 3500 BK	Black	3500mm
SWCONINTLEAD 3500 WH	White	3500mm
SWCONINTLEAD 4000 BK	Black	4000mm

SKU	Colour	Size
SWCONINTLEAD 4000 WH	White	4000mm
SWCONINTLEAD 4500 BK	Black	4500mm
SWCONINTLEAD 4500 WH	White	4500mm
SWCONINTLEAD 500 BK	Black	500mm
SWCONINTLEAD 500 WH	White	500mm
SWCONINTLEAD 5000 BK	Black	5000mm (5 Meters)
SWCONINTLEAD 5000 WH	White	5000mm (5 Meters)
SWCONINTLEAD 6000 BK	Black	6000mm
SWCONINTLEAD 6000 WH	White	6000mm

PRODUCT DESCRIPTION

Interconnecting Cable
2 Year Warranty