

### CMS INTERCONNECTING LEADS



Interconnecting leads connect wall and ceiling starters with workstations or connect power between workstations.

Standard interconnecting cables are manufactured from 3 core 2.5mm<sup>2</sup> flexible cable. They are rated at 20A and are terminated with male and female AS/NZ61535.1 compliant connectors. Where mechanical and EMC segregation from communications cabling is required within furniture and umbilicals, plastic and steel conduit casing with heat shrunk boots are also available. Leads are Halogen Free.

2 year warranty.

### ADDITIONAL INFORMATION

<b>Weight</b>	0.0000 kg
<b>Dimensions</b>	10 × 1000 × 10 mm
<b>Colour</b>	Black, White
<b>Size</b>	1000mm, 1500mm, 2000mm, 2500mm, 3000mm, 3500mm, 4000mm, 4500mm, 500mm, 5000mm ( 5 Meters ), 6000mm

**SKU:** SWINTLEADMS

**Categories:** [Rapid Wiring](#), [Rapid Wiring](#)

### VARIATIONS

SKU	Colour	Size
SWINTLEAD 1000 BK	Black	1000mm
SWINTLEAD 1000 WH	White	1000mm
SWINTLEAD 1500 BK	Black	1500mm
SWINTLEAD 1500 WH	White	1500mm
SWINTLEAD 2000 BK	Black	2000mm
SWINTLEAD 2000 WH	White	2000mm
SWINTLEAD 2500 BK	Black	2500mm
SWINTLEAD 2500 WH	White	2500mm
SWINTLEAD 3000 BK	Black	3000mm
SWINTLEAD 3000 WH	White	3000mm
SWINTLEAD 3500 BK	Black	3500mm
SWINTLEAD 3500 WH	White	3500mm

SKU	Colour	Size
SWINTLEAD 4000 BK	Black	4000mm
SWINTLEAD 4000 WH	White	4000mm
SWINTLEAD 4500 BK	Black	4500mm
SWINTLEAD 4500 WH	White	4500mm
SWINTLEAD 500 BK	Black	500mm
SWINTLEAD 500 WH	White	500mm
SWINTLEAD 5000 BK	Black	5000mm ( 5 Meters )
SWINTLEAD 5000 WH	White	5000mm ( 5 Meters )
SWINTLEAD 6000 BK	Black	6000mm
SWINTLEAD 6000 WH	White	6000mm

## PRODUCT DESCRIPTION

Interconnecting Cable  
2 Year Warranty