

HALO+ BACK TO BACK WORKSTATION WITH SCREEN

The latest addition to our height adjustable range, the Halo+ boasts a designer round leg with options for privacy screens and tidy cable trays.

With a digital control panel featuring three pre-set positions, an LED display panel, keypad safety lock, and reminder alarm setting, you can easily adjust your workstation to your preferred height with just the touch of a button.

Our innovative anti-collision and anti-tilt technology ensures that your desk is protected from accidental damage, while operating quietly with a noise emission of less than 50DB.

With a 10-year warranty, you can trust that the Halo+ is built to last and will enhance your workspace for years to come.

Choose from single, corner and back to back configurations.

SKU: H+2PEPCT1575 OWG

PRODUCT DESCRIPTION

Halo Plus Back To Back Workstation With Marble Grey 900mm H Eco Panel Screen - Natural Oak/ White Satin

1500mm W x 1500mm D x 620mm - 1270mm H (Overall)

1500mm W x 750mm D x 620mm - 1270mm H (Per User)

Overall Height AFFL including Screen: 1330mm H

https://rapidline.com.au/product/halo-ba

ck-to-back-workstation-with-screen-36/

E0 Rated 25mm T Table Top Finished In Natural Oak With Rigid Edging & 50mm D Scallop Cut Out To Rear

Round Leg Underframe Finished In White Satin Powder Coat

Fully Ducted Cable Tray With Punchout For Power & Data To be Fitted To Either External Or Internal Of Frame

1500mm W x 900mm H x 27mm T Marble Grey Eco Panel Screen With 4 x 50mm Radius Corners Digital Control Panel With 3 Pre-Set Positions, LED Display Panel, Keypad Safety Lock & Reminder Alarm Setting

Anti- Collision & Anti-Tilt Technology

Column Size: 70mm Dia

Height Range: 595mm-1245mm (Without Table Top)

Lifting Capacity: 120 Kg

Max Speed: 38mm Per Second

Adjustable Levelling Feet

Dual Motor

Desk Mounting Top Plate Size: 500mm

Steel Gauge: 3.0mm, 2.0mm & 1.5mm Used Throughout

Noise Emission: <50DB

Surge Immunity: 1kV(L1 to L2) / 2kV(L1,L2 To PE)

ESD Protection: +-4.0kV (Contact Discharge)/+-8.0kV (Air Discharge)

Input Power: 110-240V

Transformer Power:128W (.03W On Standby)

SAA and C Tick Certification

Additional Items Also Available Include:

Bluetooth Control Box (B2-BTCB)

Cable Tray Bridge (B2-B2BBR)

Flexible Cable Snake (B2-CBSNAKE)

Battery Pack (B2-BATT)

AFRDI Certified 10 Year Warranty